

Elcometer 3525 & 3530 Adjustable Baker Film Applicators

Can be used in accordance with: ASTM D 823-E



The Elcometer 3525 & 3530 Adjustable Baker Film Applicators are manufactured using the very latest machining techniques to ensure outstanding accuracy.

These Baker Film Applicators allow user to select the specific gap size required. The coating thickness gap size can be set to produce either a uniform film or film wedge. Each film applicator has thickness markings down each side for fast set up.

Available in two gap size ranges and a number of film widths, these stainless steel applicators can be used manually or with the Elcometer 4340 Motorised Film Applicator.

Technical Specification

Part Number	Model	Film Thickness μm	Film Width* mm	Certificate
K0003525M001	Elcometer 3525/1	0-100	50	o
K0003525M002	Elcometer 3525/2	0-100	75	o
K0003525M003	Elcometer 3525/3	0-100	100	o
K0003525M004	Elcometer 3525/4	0-100	150	o
K0003525M005	Elcometer 3525/5	0-100	200	o
K0003525M006	Elcometer 3525/6	0-100	250	o
K0003530M001	Elcometer 3530/1	0-250	50	o
K0003530M002	Elcometer 3530/2	0-250	75	o
K0003530M003	Elcometer 3530/3	0-250	100	o
K0003530M004	Elcometer 3530/4	0-250	150	o
K0003530M005	Elcometer 3530/5	0-250	200	o
K0003530M006	Elcometer 3530/6	0-250	250	o

Packing List

Elcometer 3525 & 3530 Adjustable Baker Film Applicator
Instruction Manual

* Add 30mm to the Film Width to calculate the total width of the applicator
o Optional Calibration Certificate available

