

elcometer® 3525 & 3530 Adjustable Baker Film Applicators


Can be used in accordance with:

ASTM D 3022

ASTM D 823

FTMS 141a M2161

FTMS 141 M6226



Manufactured using the very latest machining techniques to ensure outstanding accuracy these Baker Film Applicators allow the user to select the specific gap size required.

The gap size can be set to produce either a uniform film or a film wedge. Each film applicator has thickness markings down each side for fast set up.

Available in two gap size ranges and a number of film widths, these stainless steel applicators can be used manually or with the Elcometer 4330 and Elcometer 4340 Motorised Film Applicators.

Technical Specifications

Model	Number of Gaps	Film Gaps	Film Width	Part Number
		µm	mm	
Elcometer 3525/1	Adjustable	0 - 100	50	K0003525M001
Elcometer 3525/2	Adjustable	0 - 100	75	K0003525M002
Elcometer 3525/3	Adjustable	0 - 100	100	K0003525M003
Elcometer 3525/4	Adjustable	0 - 100	150	K0003525M004
Elcometer 3525/5	Adjustable	0 - 100	200	K0003525M005
Elcometer 3525/6	Adjustable	0 - 100	250	K0003525M006
Elcometer 3530/1	Adjustable	0 - 250	50	K0003530M001
Elcometer 3530/2	Adjustable	0 - 250	75	K0003530M002
Elcometer 3530/3	Adjustable	0 - 250	100	K0003530M003
Elcometer 3530/4	Adjustable	0 - 250	150	K0003530M004
Elcometer 3530/5	Adjustable	0 - 250	200	K0003530M005
Elcometer 3530/6	Adjustable	0 - 250	250	K0003530M006

