

Thermometer

8811

**K Type Thermometer • Economical & Accurate • Single Input Models •
IP65 Waterproof • Auto Ranging • Back Light • Sleep Mode Function •
Sleep Mode Disable • Low Battery Indication**



Features

- K type thermocouple with single input, meets IP65 grade.
- 0.1 and 1.0degree auto ranging resolution .
- Maximum/minimum/relative reading memory.
- Hold function
- °C / °F unit switchable.
- Auto power off (20min), disable sleep mode.
- Temperature coefficient:0.1 times the applicable accuracy specification per °C from 0°C to 18°C and 28°C to 50°C.
- Meter includes one K-type thermocouple probe, 9V battery, Manual, white box, rubber cap

Specification

Measurement Range :	-200 deg C to 1300 deg C	
Operation Temperature :	0 to 50 deg C (0 to 85 % RH, non-cond)	
Sampling Rates :	2.5 second	
Battery :	9 volt, bateery life : 200 hours	
Display :	37 mm x 42 mm LCD, Maximum reading 1999	
Dimensions :	181 mm x 71 mm x 38 mm	
Accuracy : (18 deg C to 28 deg C) ambient temperature :	-50 deg C to 1000 deg C	+/- (0.3% rdg + 1 deg C)
	1000 deg C to 1300 deg C	+/- (0.5% rdg + 1 deg C)
Waterproof :	IP66	



BAMR (Pty) Ltd, PO Box 23973, Claremont, 7735, South Africa
Ph : 27 (0)21 683 2100, Fax : 27 (0)21 674 1485
Email : sales@bamr.co.za Web : www.bamr.co.za