

# Elcometer 127 Keane Tator Surface Comparator and Magnifier

Can be used in accordance with: AS 3894.5, ASTM D 4417-A, SSPC PA 17



The Elcometer 127 Surface Comparators are available in sand, shot or grit surface profiles.

Each surface comparator is supplied with 5 profile grades ranging from 0.5 - 5.5 mils.

Designed for use with the Elcometer 127 illuminated magnifier, each surface comparator has a hole in the centre allowing for clear visual comparisons to be made.

5 Roughness Values per Comparator.

### **Technical Specifications**

Part Number	Description	<b>Section Profiles</b>
E1272	Elcometer 127 Sand Surface Comparator	0.5, 1, 2, 3, 4 mils
E1273	Elcometer 127 Grit Surface Comparator	1.5, 2, 3, 4.5, 5.5 mils
E1274	Elcometer 127 Shot Surface Comparator	2, 2.5, 3, 4, 5.5 mils
E1271	Illuminated magnifier (x 5) with integrated surface comparator holder	-

### **Packing List**

Elcometer 127 Keane Tator Surface Comparator and Magnifier

#### Video



## YouTube Video - How to use a Surface Comparator (Click on the image to the left to view the video)

If you are only required to quickly assess the surface profile of a blasted metal surface, then the easily transportable and easy to use Surface Comparators are the perfect choice. Put simply, comparators are a flat, steel plate which contain a number of reference surface profiles, formed on a corrosion resistant metal.

