

Elcometer 224 Digital Surface Profile Gauges

Roughness Measurement & Blast Profiles to
ASTM D 4417-B, SANS 5772, SSPC PA 17, US Navy NSI 009-32, US Navy PPI 63101-000



The Elcometer 224 provides the very latest in surface profile measuring technology for measuring profile on either flat or curved surfaces. Fast, accurate and very user friendly, the Elcometer 224 Surface Profile Gauge is available with or without memory and Bluetooth®.

The Elcometer 224 surface profile meter is available in two different models: Model B and Model T. Each surface profile gauge provides the user with increasing functionality from the entry level Elcometer 224 Model B, to the top of the range Elcometer 224 Model T, with memory, alpha-numeric batching and Bluetooth® communication.

Standard and armoured probes are available for the separate models, providing even greater measurement flexibility. Elcometer surface profile probes are supplied with a glass zero plate, calibration test foils (nominal values 125µm & 508µm and an Elcometer Test Certificate).

Features

- Accurate, immediate and repeatable results
- Integral & separate probe variants for flat and convex* surfaces
- The separate probes can now measure on pipes and tanks
- Tough tungsten carbide user replaceable tip, can be used for up to 20,000 readings
- Stores up to 150,000 readings in alpha numeric batches (Model T only)
- Auto rotating display with tap awake feature
- Cost per test is significantly lower than other test methods
- Large backlit screen makes viewing readings easy
- Digital display prevents reading interpretation errors
- Intuitive menus in multiple languages enables use straight from the box
- Dust and water resistant rugged design equivalent to IP64
- Ergonomic design for comfort during continuous use
- 2.4" Colour screen provides enhanced reading visibility at all angles
- Fast reading rate at 60+ readings per minute
- Review batch data or last 20 readings in a graph format
- Counted average mode stores the average value of a preset number of readings (Model T only)
- USB and Bluetooth® data output to ElcoMaster® (Model T only)





Integral or separate probes measure profiles up to 500 microns on flat or curved surfaces*



Ergonomic design for comfort during continuous use



2.4" Colour screen provides enhanced reading visibility at all angles

Designed with you in mind

User Friendly

- Large buttons ideal for gloved hands
- Easy to use menus in multiple languages
- High contrast colour LCD with auto rotate
- High and low reading limit indicators
- Factory calibrated for immediate use

Accurate

- Measurement capability to $\pm 5\%$
- Conforms to National & International Standards
- Temperature stable measurements
- Statistics are calculated and displayed in real time.
- Live and batch readings graph format for instant analysis

Reliability

- Repeatable and reproducible
- 2 year gauge warranty
- Supplied with fully traceable Test Certificates
- Batch & individual reading date and time stamp facility

Tough

- Sealed, heavy duty and impact resistant
- Dust and waterproof equivalent to IP64
- Scratch and solvent resistant display
- Durable gauge and probe construction
- Suitable for use in harsh environments

Efficient

- Fast reading rate of 60+ per minute
- Integral and separate probe options to suit your application on flat or curved surfaces*
- Alpha numeric batch identification
- Compatible with ElcoMaster™ 2.0 and ElcoMaster™ for Android™.
- Powersave mode with tap awake

Powerful

- Tough tungsten carbide user replaceable tip can be used for up to 20,000 readings
- USB and Bluetooth® data output
- Stores up to 150,000 readings in 2,500 batches
- Measures profiles up to 500µm



Product Features

	■ Standard Model B	□ Optional Model T
Fast, accurate reading rate; <i>50+ readings per minute</i> [^]	■	■
Repeatable & reproducible measurements	■	■
Easy to use menu structure; <i>in 30+ languages</i>	■	■
Tough, impact, water & dust resistant; <i>equivalent to IP64</i>	■	■
Bright colour screen; <i>with permanent back light</i>	■	■
Scratch & solvent resistant display; <i>2.4" (6cm) TFT</i>	■	■
Large positive feedback buttons	■	■
Flat & convex surfaces*	■	■
USB power supply; <i>via PC</i>	■	■
Test certificate	■	■
2 year gauge warranty†	■	■
Automatic rotating display; <i>0°, 90°, 180° & 270°</i>	■	■
Ambient light sensor; <i>with adjustable auto brightness</i>	■	■
Emergency light mode	■	■
Gauge software updates ¹ ; <i>via ElcoMaster® software</i>	■	■
Data output	■	■
USB; <i>to computer</i>	■	■
Bluetooth®; <i>to computer, Android™ & iOS‡ devices</i>		■
Measurement modes; <i>Immediate, Custom, Standards</i>	■	■
On screen statistics	■	■
Number of readings; η , Mean (average); \bar{x} , Standard deviation; σ ,	■	■
Highest reading; Hi, Lowest reading; Lo, Coefficient of variation; CV%		
High & low limits; <i>definable audible & visual alarms</i>		■
Number above high limit;		■
Number below low limit;		■
ElcoMaster® software & USB cable		■
Date and time stamp for each reading		■
Replaceable screen protectors	■	■
Protective case	■	■
Plastic transit case	□	■
Measurement range	0-500µm	0-500µm
On-screen calibration instructions; <i>in 30+ languages</i>	■	■
Number of batches		2.5
Gauge memory; <i>number of readings</i>	Last 5	150
Delete last reading	■2	■
Limits; <i>user definable audible & visual pass / fail warnings</i>		■
Gauge (g) or gauge & batch specific (gb) limits		gb
Batch types; <i>normal, counted average</i>		■
Batch statistics; <i>Average peak-to-valley, Average Max peak-to-valley, Standard deviation, σ; Highest reading, Hi; Lowest reading, Lo; Coefficient of variation, CV%</i>		■
Review, clear & delete batches		■
Copy batches and calibration settings		■
Alpha-numeric batch names; <i>user definable on the gauge</i>		■
Fixed batch size mode; <i>with batch linking</i>		■
Trend Graph; <i>last 20 readings</i>		■
Review batch graph		■

^ Up to 25 readings per minute for the convex probe

* USA Patent Number: 9,261,345

† The Elcometer 224 is extendable within 60 days from date of purchase, free of charge, to 2 years

¹ Internet connection required

‡ Visit www.elcometer.com/sdk to find out how to integrate Elcometer's MFi certified products to your App

² Up to the last 5 readings can be deleted

Technical Specification

Display information	2.4" (6cm) QVGA colour TFT display, 320 x 240 pixels	
Battery type	2 x AA dry cell batteries, rechargeable batteries can also be used	
Battery life	Approximately 24 hours of continuous use at 1 reading per second [#]	
Minimum Headroom	Integral:	185mm
	Separate:	See Accessories
Gauge dimensions (h x w x d)	Integral:	168 x 73 x 37mm
	Separate:	141 x 73 x 37mm
Gauge weight (including batteries)	Integral:	218g
	Separate:	161g
Measurement range	0-500µm	
Probe tip	Tungsten carbide tip 60° angle; Tip Radius: 50µm	
Operating temperature	-10 to 50°C	
Storage temperature	-10 to 60°C	
Accuracy	±5% or ±5µm	
Resolution	1µm	

* Whichever is the greater

Using default settings & lithium batteries, alkaline or rechargeable batteries may differ

† For separate gauges, the test foils, glass zero tile and protection cap are supplied with the separate probe

Part Numbers

Model Options		Description	Certificate
Part Number			
Integral Gauge	Separate Gauge[^]		
E224C-BI	E224C-BS	Elcometer 224 Model B Digital Surface Profile Gauge	•
E224C-TI	E224C-TS	Elcometer 224 Model T Digital Surface Profile Gauge	•

[^] Probes are supplied separately

• Test Certificate supplied as standard.

Separate Probes

Flat Surface Profile Probes

Supplied with either standard cables or armoured metal reinforced heavy duty cables, Elcometer surface profile probes are supplied with a glass zero plate, calibration test foils; nominal values 125 & 508µm and an Elcometer test certificate.

Technical Specification

Range: 0-500µm
Resolution: 1µm
Accuracy: ±5% or ±5µm



Probe Design	Part Number	Minimum Headroom	Minimum Sample Diameter	Certificate
Flat Surface: Standard	T224C500US	125mm	25mm	•
Flat Surface: Armoured	T224C500UARM	165mm	25mm	•

Convex Surface Profile Probes

Supplied with either standard cables or armoured metal reinforced heavy duty cables, Elcometer convex surface profile probes are supplied with a glass zero tile, calibration test foils nominal values 125 & 508µm and an Elcometer test certificate.

Technical Specification

Range: 0-500µm
 Resolution: 1µm
 Accuracy: ±5% or ±5µm



Probe Design	Part Number	Minimum Headroom	Minimum Sample Diameter	Certificate
Convex Surface: Standard*	T224C500UX	135mm	75mm	•
Convex Surface: Armoured*	T224C500UXARM	175mm	75mm	•

* USA Patent Number: 9,261,345, Elcometer 224 probes are covered by a 1-year warranty

Accessories


Part Number	Description
T22420053	Replacement Probe Tips; Pack of 2 with Fixing Tool
T22420095	Replacement Probe Tips; Pack of 5
T22419793	Probe Tip Protection Cap
T22421882C	Certified Calibration Test Kit: 125 & 500µ, Calibration Foils, Glass Zero Tile & Cal Certificate
T22420072	Glass Zero Tile
T99921325	USB Cable
T99924797	USB Bluetooth Adaptor (V2.0+) - for PC's without Bluetooth
T99922341	Self Adhesive Screen Protectors (x10)
T22423371	Plastic Transit Case

Packing List

Elcometer 224 gauge
 Glass zero tile
 2 x calibration foils†
 Wrist harness
 Plastic Transit Case (T)
 Protective Case
 Screen protector
 Probe protection cap†
 2 x AA batteries
 Test certificate
 Operating instructions
 USB cable (T)
 ElcoMaster® software (T)



How to measure surface profile



1. Ensure probe is 90° to substrate to ensure accurate readings and calibrate the gauge on a glass zero tile.
2. To take one spot measurement, take either 5 or 10 readings within a 100mm diameter area.
3. The measurement displayed is either the average peak-to-valley height or the maximum reading of the 5 or 10 readings, depending on which measurement mode you have selected.
4. To establish the average surface profile of an area, record 5 spot measurements for each 1m x 1m area.