

# Elcometer 3550 Single Sided & Elcometer 3540 Four Sided Film Applicators

Can be used in accordance with: ASTM D 823-E



The Elcometer 3550 Single Sided & Elcometer 3540 Four Sided Film Applicators are easy to clean gauges manufactured to the highest accuracy.

Precision ground stainless steel Single Sided and Four Sided Film Applicators have a flat edged prismatic body making them suitable for coatings applied to a flat and relatively strong substrate.

The Elcometer 3550 Single Sided Film Applicator has 1 film thickness, whereas the Elcometer 3540 Four Sided Film Applicator has 4 thicknesses per applicator.

Both versions are available in a range of film widths and can be used with the Elcometer 4340 Motorised Film Applicator.

## Technical Specification

Part Number	Model	Film Thickness $\mu\text{m}$	Film Width* mm	Certificate
K0003550M001	Elcometer 3550/1	50	50	o
K0003550M002	Elcometer 3550/2	50	75	o
K0003550M003	Elcometer 3550/3	50	150	o
K0003550M201	Elcometer 3550/1	75	50	o
K0003550M202	Elcometer 3550/2	75	75	o
K0003550M203	Elcometer 3550/3	75	150	o
K0003540M001	Elcometer 3540/1	50, 100, 150, 200	50	o
K0003540M002	Elcometer 3540/2	50, 100, 150, 200	75	o
K0003540M003	Elcometer 3540/3	50, 100, 150, 200	100	o
K0003540M004	Elcometer 3540/4	50, 100, 150, 200	150	o
K0003540M005	Elcometer 3540/5	50, 100, 150, 200	200	o
K0003540M006	Elcometer 3540/6	50, 100, 150, 200	250	o

\* Add 40mm to the Film Width to calculate the total width of the applicator  
o Optional Calibration Certificate available

## Packing List

Elcometer 3550 Single Sided & Elcometer 3540 Four Sided Film Applicators  
Instruction Manual

