

elcometer® **Bird Film Applicators** **3550 and 3540**

Can be used in accordance with:

ASTM D 3022

ASTM D 823

FTMS 141a M2161

FTMS 141a 4122.1

FTMS 141a 2162



These easy to clean gauges are manufactured to the highest accuracy. Precision ground stainless steel Bird Film Applicators have a flat edged prismatic body making them suitable for various products applied to a flat and relatively strong substrate.

The Elcometer 3550 Bird Film Applicator has 2 gap sizes, whereas the Elcometer 3540 has 4 gap sizes per applicator.

Both versions are available in a range of film widths and can be used with the Elcometer 4330 and Elcometer 4340 Motorised Film Applicators.

Technical Specifications

Model	Number of Gaps	Film Gaps	Film Width	Part Number
		µm	mm	
Elcometer 3550/1	1	50	50	K0003550M001
Elcometer 3550/2	1	50	75	K0003550M002
Elcometer 3550/3	1	50	100	K0003550M003
Elcometer 3550/1	1	75	50	K0003550M201
Elcometer 3550/2	1	75	75	K0003550M202
Elcometer 3550/3	1	75	100	K0003550M203
Elcometer 3540/1	4	50, 100, 150, 200	50	K0003540M001
Elcometer 3540/2	4	50, 100, 150, 200	75	K0003540M002
Elcometer 3540/3	4	50, 100, 150, 200	100	K0003540M003
Elcometer 3540/4	4	50, 100, 150, 200	150	K0003540M004
Elcometer 3540/5	4	50, 100, 150, 200	200	K0003540M005
Elcometer 3540/6	4	50, 100, 150, 200	250	K0003540M006

Other gaps and film widths are available upon request

