

# elcometer® 2434 to 2437 Frikmar Viscosity Cups with Handle

Can be used in accordance with:

ISO 2431  
 DIN 53211  
 ASTM D1200  
 AFNOR NTT 30-014  
 DIN 53224  
 NF T 30 070  
 NF EN 535  
 ASTM D1525  
 NBN T22-108



Thanks to its handle, this cup is very easy to use and performs quick controls in workshops or during the manufacturing process. Ideal for measuring the consistency of paints, varnishes and similar products.

The cup is first dipped into the product to be measured, then empties through the orifice. The measured kinematic viscosity is generally expressed in seconds (s) flow time, which can be converted to centistokes (cSt), if standard stipulates conversion method.

Several ranges are available, according to standards; from 7 to 1100cSt.

## Technical Specifications

Model	Cup Number	Viscosity Cup Type	Range Centistokes (cSt)*	Part Number
Elcometer 2434/1	2	DIN	-	K0002434M001
Elcometer 2434/2	4	DIN	DIN 53211	K0002434M002
Elcometer 2434/3	6	DIN	-	K0002434M003
Elcometer 2434/4	8	DIN	-	K0002434M004
Elcometer 2435/1	4	ASTM	ASTM D1200	K0002435M001
Elcometer 2436/1	4	AFNOR NTT	AFNOR NTT 30-014	K0002436M001
Elcometer 2437/1	2	ISO DIN NF NBN ASTM	ISO 2431	K0002437M001
Elcometer 2437/2	3	ISO DIN NF NBN ASTM	DIN 53224	K0002437M002
Elcometer 2437/3	4	ISO DIN NF NBN ASTM	NF T 30 070	K0002437M003
Elcometer 2437/6	5	ISO DIN NF NBN ASTM	NF EN 535	K0002437M006
Elcometer 2437/4	6	ISO DIN NF NBN ASTM	ASTM D1525	K0002437M004
Elcometer 2437/5	8	ISO DIN NF NBN ASTM	NBN T22-108	K0002437M005
<b>Accessories</b>	2400 Viscosity Conversion Disk			KT002400N003
	Stopwatches			See Stopwatches
	Viscosity Standard Oils for Calibration			See Viscosity Standard Oils

Elcometer provide a viscosity recalibration service using state of the art climate controlled facilities.

\*for information only