

elcometer® 995 Coated Thickness Standards



These hard wearing and durable coated standards are mounted in an attractive protective folder and provide the user with an ideal method to accurately measure the performance of their coating thickness gauge.

- $\pm 2\%$ Accuracy, supplied with calibration certificate as standard
- Available in Ferrous (F) and Non-Ferrous (NF) substrates
- Two piece, three piece, and four piece versions available
- Each standard is individually serial numbered for traceability to National Standards
- Can be re-certified by Elcometer to meet your ISO requirements
- Standards available in a range of thicknesses
- Special thicknesses can be supplied to meet your particular needs

Technical Specifications and Part Numbers

COATED THICKNESS STANDARDS

2-Piece Thickness Values (Ferrous)	Zero, 50, 250 μm	T995166001
2-Piece Thickness Values (Non-Ferrous)	Zero, 50, 125 μm	T995166011
3-Piece Thickness Values (Ferrous)*	100, 300, 500 μm	T99518510
4-Piece Thickness Values (Ferrous)	Zero, 40, 75, 125, 175 μm	T995111262
4-Piece Thickness Values (Non-Ferrous)	Zero, 40, 75, 125, 175 μm	T995111271
4-Piece Thickness Values (Ferrous)	Zero, 50, 80, 125, 200 μm	T995111263
4-Piece Thickness Values (Ferrous)	Zero, 50, 150, 250, 500 μm	T995111261

* Designed specifically for use with the Elcometer 211 Mechanical Coating Thickness Gauges