# Novo Shade Duo 45 / 0° Reflectometer

## Complies with ISO 2814, 6504, BS 3900-D4, D7, ASTM E97, E1347, D4214, D2805, ASTM D589

The new Novo-Shade Duo is a dual function reflectometer for measuring shade and opacity with 45/0° geometry.

#### Features

- Automatic calibration mode for safe and fast calibration ٠
- Continuous-read feature for guickly checking large surfaces for colour or opacity variations
- Statistical analysis of stored readings gives an instant indication of batch quality
- Download readings to pc for further analysis with Novo-Soft™ included as standard
- Extended two year warranty free for registered products
- Extended life light source over 10 years operation under normal conditions

#### Shade mode

- Shade of paints, inks and coatings •
- Fading of textiles and plastics •
- Chalking of paint
- Efficiency of detergents and bleaching agents
- Whiteness of recycled paper
- Cleanliness and oxidisation on metal surfaces

#### Opacity mode

- Hiding power of paints, inks and coatings
- Transparency of plastic film
- Opacity of paper

#### Accessories

- NPL traceable calibration standard
- RS232 data cable
- Protective instrument case
- 4 x AA batteries
- Novo-Soft™ QA software CD

#### Specifications

| Resolution       | 0.10%         | Languages        |
|------------------|---------------|------------------|
| Repeatability    | 0.20%         | Dimensions       |
| Reproduceability | 0.50%         | Weight           |
| Battery life     | 3000 readings | Measurement area |

Measurement units

Shade mode

0% = black - no reflectance100% = brilliant white - full reflectance

Opacity mode 0% = completely transparent 100% = fully opaque

### Part Numbers

Statistical Novo-Shade Duo 45/0 Reflectometer (No Kit) NSD NSD / Kit Statistical Novo-Shade Duo 45/0 Reflectometer (Kit includes Draw Down bar, Glass bed, Test cards)



BAMR (Pty) Ltd, PO Box 23973, Claremont, 7735, South Africa Ph: 27 (0)21 683 2100, Fax: 27 (0)21 674 1485 Email : sales@bamr.co.za. Web : www.bamr.co.za





UK, FR, DE, NL, ES, IT 125 x 50 x 100mm 470g 15 x 10mm ellipse